
## Panoramica

### Informazioni sul prodotto



# 15EDGRHM-3.81-10030000501

Pluggable terminal blocks,Rated current:7A.Rated voltage （Ⅱ/2）:250V,pitch:3.81mm,Color:green,Contact surface :Tin

### Vantaggi del prodotto

☑ Universal installation method to ensure a high degree of flexibility in device design
☑ Multi-layer wire connection can achieve higher contact density

### Certificazione del prodotto

## Dati tecnici

### Disegno del prodotto

### Modello 3D

### Processing notes

| | |
|---|---|
| Process | Wave soldering/manual soldering |

### Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 300V |
| Rated current (B) | 8A |

### Electrical parameters IEC

| | |
|---|---|
| Rated voltage | 250V |
| Rated current | 7A |
| Rated voltage(Ⅱ/2) | 250V |
| Rated surge voltage(Ⅱ/2) | 2.5KV |

## Item properties

| | |
|---|---|
| Connection direction | 0° |
| Type of installation | PCB welding |
| Pin arrangement | Double-row in a straight line |
| Pitch | 3.81mm |
| Number of potentials | 4 |
| Pluggable or not | Yes |
| Number of rows | 1 |

## Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | Copper alloy |
| Contact zone metal surface | tin-plated |
| Insulation Materials | PA66 |
| Insulating material group | Ⅰ |
| Flammability rating | UL94V-0 |

## Mechanical tests

| | |
|---|---|
| Test Specification | IEC60947/UL1059 |

## Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -40℃~105℃ |

# Accessori

## Tool

| | |
|---|---|
| Screwdriver | / |
| Operating tool | / |

## Accessories

| | |
|---|---|
| Coding strip | / |
| Bridge | / |
| Marking strip | / |
| Others | 15EDG-PWI |

## Dati aziendali

| | |
|---|---|
| numero d'ordine | 10030000501 |
| Unità di imballaggio | 445 |
| Quantità di ordine minimo | 30 |
| Peso dei prodotti (senza imballaggio) | 7.15 |