Overview

Product information



Relay module-DM50-RMUS-04-PN-1-44-00A(H)-30030000107

Subminiature Relay Module,with relay Socket ,4 relays can be installed,with relay Socket,with indicator light,panasonic relay,PNP or NPN signal can be input (Please contact us for relay replacement)

Product advantages

☑ Each signal channel and power supply voltage have LED status indicators
☑ Pluggable subminiature relay, with a set of normally open contacts, one-to-one output at the output
☑ Suitable for NPN, PNP controller
☑ Freewheeling diode for each signal path
☑ Compact size, saving space in the cabinet

Product certification

Technical data

Product drawing

3D model

Overview

Installation location	Arbitrary
Number of channels	4
Shell Insulation Materials	PC
color	black

Dimension

width	60mm
Height	31mm
length	65.6mm

Enter technical data

Rated input voltage	24VDC
Input voltage range relative to UN	0.9....1.1
protected name	Polarity protection
Protection circuits/components	Polarity Protection Diode
Status display/channel	green

Export technical data

contact type	1NO
Maximum switching voltage	240VAC 30VDC
Limit continuous current	5A
Fault monitoring (open circuit/short circuit)	no

Output connection data

connection name	output
Connection method	screw connection
Stripping length	6-7mm
thread	M3
connection volume	1
number of digits	8
Hard conductor cross section	1.0 ... 2.5mm²
Flexible conductor cross section	1.0 ... 2.5mm²
Connectable guide cross section AWG	28...12AWG

Enter connection data

connection name	enter
Connection method	screw connection
Stripping length	6-7mm

thread	M3
connection volume	1
number of digits	6
Hard conductor cross section	1.0 ... 2.5mm²
Flexible conductor cross section	1.0 ... 2.5mm²
Connectable guide cross section AWG	28...12AWG

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III

Accessories

Business data

Order number	30030000107
Packing unit	2
Minimum order quantity	10
Products weight (without packaging)	80