Overview

Product information



Relay Socket-DSRT-05A-3-00A(H)-30020000057

DSRT Relay Socket, used for 1PDT relay, screw connection

Product advantages

☑ Screw base relay socket
☑ Safe isolation between coil and contacts
☑ 16A ,1PDT

Product certification

Technical data

Product drawing

3D model

Dimension

width	16mm
length	73.3mm
Depth including bracket	29.5mm

Environmental data

Ambient temperature (operation)	-45℃～+85℃
Ambient temperature (storage / transport)	-40℃~+85℃

Technical data

Rated voltage UN	300V

Rated current IN	16A
Installation location	Arbitrary
Assembly instructions	DIN35 rail

Connection data 1

Connection name	enter
Connection method	Screw connection
Stripping length	7-8mm
screw thread	M3
Cross section of flexible conductor	0.5-2.5mm²
Connectable guide cross section AWG	20-14AWG

Connection data 2

Connection name	Output
Stripping length	7-8mm
Cross section of flexible conductor	0.5-2.5mm²
Connectable guide cross section AWG	20-14AWG
Connection method	Screw connection

Accessories

Accessory

Bridge	DFJ8-16-13-00Z(H)
Function Module	DMD-L-6/24V-00A(H)

Business data

Order number	30020000057
Packing unit	20 SKT

Minimum order quantity	20 SKT
Products weight (without packaging)	27g