Panoramica

Informazioni sul prodotto



15EDGKDGB-3.5-10020007412

Pluggable terminal blocks,Rated current:12A.Rated voltage （III/2）:250V,pitch:3.5mm,Color:green,Contact surface :Tin

Vantaggi del prodotto

☑ Suitable for a variety of sockets
☑ PUSH-IN connection technology, quick wiring
☑ Both sides with operating rods, easy to pull out

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

Packaging information

Type of packaging	bag packaging

Connection capacity

Conductor cross section solid	0.2~1.5mm²
Conductor cross section flexible	0.2~1.5mm²
AWG	28~16AWG
Strip length	9mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	300V

Rated voltage (D)	300V
Rated current (B)	8A
Rated current (D)	8A
Rated current (C)	8A

Electrical parameters IEC

Rated voltage	250V
Rated current	12A
Rated voltage(III/2)	250V
Rated surge voltage(III/2)	2.5KV

Item properties

Connection method	Push-in spring connection
Screwdriver	Slotted screwdriver
Pitch	3.5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Relative tracking index CTI	600V
Shell color	green
Insulating material group	I

Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃

Accessori

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Dati aziendali

numero d'ordine	10020007412
Unità di imballaggio	600
Quantità di ordine minimo	600
Peso dei prodotti (senza imballaggio)	2.75