DEGSON

Panoramica

Informazioni sul prodotto



9EDGKD-7.62-10020007234

Pluggable terminal blocks,Rated current:20A.Rated voltage （III/2）:630V,pitch:7.62mm,Color:black,Contact surface :Tin

Vantaggi del prodotto

☑ Compact design, save space in the cabinet
☑ PUSH-IN connection technology, fast wiring
☑ Safety buckle design, stable connection

Certificazione del prodotto

c UL us

Dati tecnici

Disegno del prodotto

Modello 3D

Packaging information

Type of packaging	bag packaging

Connection capacity

Conductor cross section solid	0.5~4mm²
Conductor cross section flexible	0.5~2.5mm²
AWG	20~2AWG
Strip length	10mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V

Rated current (B)	20A
Rated current (C)	20A

Electrical parameters IEC

Rated voltage	630V
Rated voltage(III/3)	400V
Rated current	20A
Rated voltage(III/2)	630V
Rated voltage(II/2)	1000V
Rated surge voltage(III/3)	6KV
Rated surge voltage(III/2)	6KV
Rated surge voltage(II/2)	6KV

Item properties

Connection method	Push-in spring connection
Pitch	7.62mm
Number of potentials	3
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Relative tracking index CTI	400V
Glow Wire Flammability Index GWFI	850

Shell color	Black
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059

Environmental data

Ambient temperature (operation)	-40℃~120℃

Accessori

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Dati aziendali

numero d'ordine	10020007234
Unità di imballaggio	
Quantità di ordine minimo	
Peso dei prodotti (senza imballaggio)	