Panoramica

Informazioni sul prodotto



DG332J-THR-5.0-10030010305

Needle connector，Rated current：12A，Rated voltage（III/2）：250V，Pitch：5.0mm，Color：Black，Contact surface：Tin

Vantaggi del prodotto

☑ Adapt to multi-type plugs, device design is highly flexible
☑ Plastic parts are made of high temperature material,which can meet THR process
☑ Universal installation method

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

Processing notes

Process	Reflow soldering/wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	10A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	250V

Rated current	12A
Rated voltage(III/2)	250V
Rated power frequency voltage(1min)	2KV

Item properties

Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Pitch	5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	High temperature resistant materials
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059

Environmental data

Ambient temperature (operation)	-40℃~130℃

Accessori

Dati aziendali

numero d'ordine	10030010305
Unità di imballaggio	
Quantità di ordine minimo	
Peso dei prodotti (senza imballaggio)	