
Panoramica

Informazioni sul prodotto



5EDGKG-10.16-10010002922

Pluggable terminal blocks,Rated current:57A.Rated voltage （III/3）:600V,pitch:10.16mm,Color:green,Contact surface :Tin

Vantaggi del prodotto

☑ Adapt to multi-type sockets, device design is highly flexible
☑ Keying parts can be installed
☑ Universal installation method, suitable for various situations

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

Connection capacity

Conductor cross section solid	0.5~10mm²
Conductor cross section flexible	0.5~10mm²
AWG	20~6AWG
Torque	1.2N.m
Strip length	11mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V

Rated current (B)	52A
Rated current (D)	5A
Rated current (C)	52A

Electrical parameters IEC

Rated voltage	600V
Rated voltage(III/3)	600V
Rated current	57A
Rated surge voltage(III/3)	6KV

Item properties

Connection direction	0°
Screwdriver	Slotted screwdriver
screw thread	M4
Pitch	10.16mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	Silver plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃

Accessori

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Dati aziendali

numero d'ordine	10010002922
Unità di imballaggio	120
Quantità di ordine minimo	30
Peso dei prodotti (senza imballaggio)	15.87