## Overview

### Product information



# D16B-SE-4g-PG21-21010000062

16BHoods,Four levers,side entry,PG21 Thread hole

### Product advantages

☑Metal or high-strength plastic material, resistant to high-strength mechanical shock;
☑Various installation methods and outlet directions to meet on-site wiring requirements;
☑Snap-in combination structure, dustproof, waterproof, easy operation;

### Product certification

## Technical data

### Product drawing

### 3D model

### Marking

| | |
|---|---|
| classification | Upper Housing/base |
| Series | B |
| Type | Top housing |
| Specification | Low structure |

### Versions

| | |
|---|---|
| Dimension | 16B |
| locking Category | Double lock |
| Wiring method | Side entry |
| Thread specification | 1x PG21 |

### Material characteristics

| | |
|---|---|
| RoHS | conform |
| Material (upper housing/base) | Die-cast aluminium alloy |
| Material(upper housing/base) | spray |
| Color (upper housing/base) | Grey（RAL 7037） |

Technical specification

| | |
|---|---|
| Limiting temperatures | -40℃~+125℃ |
| IP class | IP65 |

## Accessories

## Business data

| | |
|---|---|
| Order number | 21010000062 |
| Packing unit | 100 |
| Minimum order quantity | 1 |
| Products weight (without packaging) | 189 |