## Przegląd

### Informacje o produkcie



# 2EDGJ-5.08-10030001090

Pluggable terminal blocks,Rated current:15A.Rated voltage （III/2）:320V,pitch:5.08mm,Color:green,Contact surface :Tin

### Zalety produktu

☑ Universal installation method to ensure a high degree of flexibility in device design
☑ The plug direction is perpendicular to PCB

### Certyfikacja produktu

## Dane techniczne

### Rysunek produktu

### Model 3D

### Processing notes

| | |
|---|---|
| Process | Wave soldering/manual soldering |

### Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 300V |
| Rated voltage (D) | 300V |
| Rated current (B) | 18A |
| Rated current (D) | 10A |

### Electrical parameters IEC

| | |
|---|---|
| Rated voltage | 320V |
| Rated voltage(III/3) | 250V |

| | |
|---|---|
| Rated current | 15A |
| Rated voltage(III/2) | 320V |
| Rated voltage(II/2) | 630V |
| Rated surge voltage(III/3) | 4KV |
| Rated surge voltage(III/2) | 4KV |
| Rated surge voltage(II/2) | 4KV |

Item properties

| | |
|---|---|
| Connection direction | 90° |
| Type of installation | PCB welding |
| Pin arrangement | Single row in a straight line |
| Pitch | 5.08mm |
| Number of potentials | 2 |
| Pluggable or not | Yes |
| Number of rows | 1 |

Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | Copper alloy |
| Contact zone metal surface | tin-plated |
| Insulation Materials | PA66 |
| Insulating material group | I |
| Flammability rating | UL94V-0 |

Mechanical tests

| | |
|---|---|
| Test Specification | IEC61984/ UL1059 |

Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -40℃~105℃ |

## Akcesoria

### Tool

| | |
|---|---|
| Screwdriver | / |
| Operating tool | / |

### Accessories

| | |
|---|---|
| Coding strip | / |
| Bridge | / |
| Marking strip | / |
| Others | / |

## Dane biznesowe

| | |
|---|---|
| numer zamówienia | 10030001090 |
| Jednostka opakowania | 2400 |
| Minimalna ilość zamówienia | 30 |
| Waga produktów (bez opakowania) | 0.8021 |