
概要

製品情報



PC35-PE-11010000067

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm² - 35 mm², AWG: 18 - 1/0, Width: 15.2 mm, Color: green-yellow, Mounting type: NS 35/7.5, NS 35/15

製品の特長

☑Screw connection technology, reliable connection；
☑Grounding structure, protection circuit；
☑Copper alloy material, good corrosion resistance；
☑Can be matched with marker strips to avoid incorrect insertion of wires。

製品認証

CE

技術データ

製品チャート

3Dモデル

Wiring data

Screw type	Slotted screw
2 flexible conductors with a TWIN ferrule	0.75-10mm²
Strip length	18~19mm
Conductor cross section solid	0.2~35mm²
Conductor cross section flexible	0.2~35mm²
Conductor cross section solid AWG	18~1/0
screw thread	M6
Tightening torque	2.5N.m

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated surge voltage	8KV

Environmental protection

REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	63.25mm
NS 35/15 Height	70.75mm
length	50mm
width	15.2mm
Height	61.8mm

Overview

Connection method	screw connection
Number of rows	1
number of connections	2
Open-end side panels	no
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

アクセサリ

Accessories

Slotted screwdriver size (Blade thickness x Width)	1×6.5

Fixed bridge	/
Insertion bridge	EB2-15 / EB3-15 / EB10-15
End cover	/
Separating disk	/
Partition plate	/

Marker

Top marker	/
Marker	ZT12
Marker support	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Marking & Installation

Marking strip	ZB10
Marker cards	DBE-1

Accessories

Bridge	EBXX-15
End clamp	E-WS
DIN rail	NS35/7.5-1000-00A(H)

ビジネスデータ

注文番号	11010000067
パッキングユニット	20
最小注文数量	20

1個あたりの重量（梱包を含めない）	85.72