概要

## 製品情報



# PC35-11010000059

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Rated voltage: 1000 V,Rated current: 125 A, Number of connectors: 2, Number of potentials: 1, Cross section: 18 mm² - 1/0 mm², AWG: 28 - 12, Width: 15.2 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

## 製品の特長

☑Screw connection technology, reliable connection；
☑Equipped with fixed parts and bridge parts, circuit connection test is more flexible；
☑Copper alloy material, good corrosion resistance；
☑Can be matched with marker strips to avoid incorrect insertion of wires。

## 製品認証

技術データ

## 製品チャート

## 3Dモデル

## Wiring data

| | |
|---|---|
| Screw type | Slotted screw |
| 2 flexible conductors with a TWIN ferrule | 0.75-10mm² |
| Strip length | 15~16mm |
| Conductor cross section solid | 0.2~35mm² |
| Conductor cross section flexible | 0.2~35mm² |
| Conductor cross section solid AWG | 18~1/0 |
| screw thread | M6 |
| Tightening torque | 2.5N.m |

| Environmental conditions | |
|---|---|
| Ambient temperature (operation) | -40 °C ~ 105 °C（depending on derating curve） |
| Relative humidity (storage/transport) | 25%~75% |
| **UL Electrical parameters** | |
| Rated current | 150A |
| **IEC Electrical parameters** | |
| Rated voltage (III / 3) | 1000V |
| Rated current (III / 3) | 125A |
| Rated surge voltage | 8KV |
| **Environmental protection** | |
| REACh SVHC | Lead 7439-92-1 |
| RoHS | No excessive harmful substances |
| **Dimension** | |
| NS 35/7,5 Height | 63.25mm |
| NS 35/15 Height | 70.75mm |
| length | 50mm |
| width | 15.2mm |
| Height | 62mm |
| **Overview** | |
| Connection method | screw connection |
| Number of rows | 1 |
| number of connections | 2 |
| Open-end side panels | no |
| Insulation Materials | PA |
| Flame retardant grade, in line with UL 94 | V0 |

アクセサリ

## Accessories

| | |
|---|---|
| Slotted screwdriver size (Blade thickness x Width) | 1×6.5 |
| Fixed bridge | FBIXX-15 |
| Insertion bridge | EB2-15 / EB3-15 / EB10-15 |
| End cover | / |
| Separating disk | TS-K |
| Partition plate | / |

## Marker

| | |
|---|---|
| Top marker | / |
| Marker | ZT12 |
| Marker support | / |

## Installation

| | |
|---|---|
| End clamp | E-WS N / E-PC-1100A |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2 |
| DIN rail | NS35/7.5 & NS35/15 |

## Marking & Installation

| | |
|---|---|
| Marking strip | ZB10 |
| Marker cards | DBE-1 |

## Accessories

| | |
|---|---|
| Bridge | FBIXX-15 |
| End clamp | E-WS |
| DIN rail | NS35/7.5-1000-00A(H) |

ビジネスデータ

| | |
|---|---|
| 注文番号 | 11010000059 |
| パッキングユニット | 30 |
| 最小注文数量 | 30 |
| １個あたりの重量（梱包を含めない） | 54.815 |