
概要

製品情報



PCDK4-11010000117

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Rated voltage: 630 V,Rated current: 32 A, Number of connectors: 3, Number of potentials: 1, Cross section: 0.2 mm² - 4 mm², AWG: 24 - 10, Width: 6.2 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

製品の特長

☑Screw connection technology, reliable connection；
☑Equipped with fixed parts and bridge parts, circuit connection test is more flexible；
☑Copper alloy material, good corrosion resistance；
☑Can be matched with marker strips to avoid incorrect insertion of wires。

製品認証

技術データ

製品チャート

3Dモデル

Wiring data

Screw type	Slotted screw
2 flexible conductors with a TWIN ferrule	0.5-1.5mm²
Strip length	7~8mm
Conductor cross section solid	0.2~4mm²
Conductor cross section flexible	0.2~4mm²
Conductor cross section solid AWG	24~10
screw thread	M3
Tightening torque	0.5N.m

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated voltage (III / 3)	630V
Rated current (III / 3)	32A
Rated surge voltage	6KV

Environmental protection

REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	48.4mm
End plate width	1.5mm
NS 35/15 Height	55.9mm
length	63.5mm
width	6.2mm
Height	47mm

Overview

Connection method	screw connection
Number of rows	1
number of connections	4
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

アクセサリ

Accessories

Slotted screwdriver size (Blade thickness x Width)	0.6×3.5
Fixed bridge	FBIXX-6
Insertion bridge	EB2-6 / EB3-6 / EB10-6
End cover	D-PCDK2.5
Separating disk	TS-KK3
Partition plate	/

Marker

Top marker	/
Marker	ZB6
Marker support	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Marking & Installation

Marking strip	ZB6
Marker cards	DBE-1

Accessories

End cover	D-PCDK2.5
Grouping Partition plate	TS-KK3
Bridge	FBIXX-6
End clamp	E-WS
DIN rail	NS35/7.5-1000-00A(H)

ビジネスデータ

注文番号	11010000117
パッキングユニット	50
最小注文数量	50
１個あたりの重量（梱包を含めない）	14.879