
概要

製品情報



PCIK35-11010000122

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Rated voltage: 800 V,Rated current: 125 A, Number of connectors: 2, Number of potentials: 1, Cross section: 18 mm² - 1/0 mm², AWG: 28 - 12, Width: 15 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

製品の特長

☑Screw connection technology, reliable connection；
☑Equipped with fixed parts and bridge parts, circuit connection test is more flexible；
☑Copper alloy material, good corrosion resistance；
☑Can be matched with marker strips to avoid incorrect insertion of wires。

製品認証

CE

技術データ

製品チャート

3Dモデル

Wiring data

Screw type	Slotted screw
2 flexible conductors with a TWIN ferrule	6-10mm²
Strip length	15~16mm
Conductor cross section solid	0.2~35mm²
Conductor cross section flexible	0.2~35mm²
Conductor cross section solid AWG	18~1/0
screw thread	M6
Tightening torque	2.5N.m

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated voltage (III / 3)	800V
Rated current (III / 3)	125A
Rated surge voltage	8KV

Environmental protection

REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	51.25mm
NS 35/15 Height	58.75mm
length	55mm
width	15mm
Height	50mm

Overview

Connection method	screw connection
Number of rows	1
number of connections	2
Open-end side panels	no
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

アクセサリ

Accessories

Slotted screwdriver size (Blade thickness x Width)	1×6.5
Fixed bridge	FBIXX-15
Insertion bridge	EB2-15 / EB3-15 / EB10-15
End cover	/
Separating disk	TS-K
Partition plate	/

Marker

Top marker	/
Marker	ZT12
Marker support	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Marking & Installation

Marking strip	ZB10
Marker cards	DBE-1

Accessories

Bridge	FBIXX-15
Grouping Partition plate	TS-K
End clamp	E-WS
DIN rail	NS35/7.5-1000-00A(H)

ビジネスデータ

注文番号	11010000122
パッキングユニット	20
最小注文数量	20
1個あたりの重量（梱包を含めない）	43.263