
概要

## 製品情報



# PCTK6-11010000146

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Rated voltage: 400 V,Rated current: 41 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.5 mm² - 6 mm², AWG: 26 - 10, Width: 8.2 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

## 製品の特長

☑Test disconnect terminal block；
☑Screw connection technology, reliable connection；
☑Equipped with fixed parts and bridge parts, circuit connection test is more flexible；
☑Copper alloy material, good corrosion resistance；
☑Can be matched with marker strips to avoid incorrect insertion of wires。

## 製品認証

技術データ

## 製品チャート

## 3Dモデル

## Wiring data

| | |
|---|---|
| Screw type | Slotted screw |
| 2 flexible conductors with a TWIN ferrule | 0.5-1.5mm² |
| Conductor cross section flexible (ferrule with plastic sleeve) | 0.5-4mm² |
| Strip length | 13~14mm |
| Conductor cross section solid | 0.5~6mm² |
| Conductor cross section flexible | 0.5~6mm² |
| Conductor cross section solid AWG | 26~10 |

| | |
|---|---|
| screw thread | M4 |
| Tightening torque | 1.2N.m |

Environmental conditions

| | |
|---|---|
| Ambient temperature (operation) | -40 °C ~ 105 °C（depending on derating curve） |
| Relative humidity (storage/transport) | 25%~75% |

IEC Electrical parameters

| | |
|---|---|
| Rated voltage (III / 3) | 400V |
| Rated current (III / 3) | 41A |
| Rated surge voltage | 6KV |

Environmental protection

| | |
|---|---|
| REACh SVHC | Lead 7439-92-1 |
| RoHS | No excessive harmful substances |

Dimension

| | |
|---|---|
| NS 35/7,5 Height | 51.75mm |
| End plate width | 2mm |
| NS 35/15 Height | 59.25mm |
| length | 72mm |
| width | 8.2mm |
| Height | 50.5mm |

Overview

| | |
|---|---|
| Connection method | screw connection |
| Number of rows | 1 |
| number of connections | 2 |
| Open-end side panels | Yes |
| Insulation Materials | PA |

| | |
|---|---|
| Flame retardant grade, in line with UL 94 | V0 |

アクセサリ

Accessories

| | |
|---|---|
| Slotted screwdriver size (Blade thickness x Width) | 1×4 |
| Fixed bridge | FBXX-RTK/S |
| Switch bridges | SBXX-RTK/S |
| Insertion bridge | EB2-8 / EB3-8 / EB10-8 |
| End cover | D-PCTK6 |
| Separating disk | / |
| Partition plate | / |

Marker

| | |
|---|---|
| Top marker | / |
| Marker | ZB8 |
| Marker support | / |

Installation

| | |
|---|---|
| End clamp | E-WS N / E-PC-1100A |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2 |
| DIN rail | NS35/7.5 & NS35/15 |

Marking & Installation

| | |
|---|---|
| Marking strip | ZB8 |
| Marker cards | DBE-1 |

Accessories

| | |
|---|---|
| End cover | D-PCTK6 |
| Bridge | FBXX-RTK/S |

| | |
|---|---|
| End clamp | E-WS |
| DIN rail | NS35/7.5-1000-00A(H) |

## ビジネスデータ

| | |
|---|---|
| 注文番号 | 11010000146 |
| パッキングユニット | 50 |
| 最小注文数量 | 50 |
| 1個あたりの重量（梱包を含めない） | 33.297 |