Panoramica

Informazioni sul prodotto



Interface module-DM50-DG-8-10-1N-00A(H)-30040000012

8 positions output module,I/O interface module,can access binary or ternary NPN signal,with indicator light,with screw connector,can be installed on DIN35 rail

Vantaggi del prodotto

Quick-plug wiring
Screw connection
Can be connected to 2 or 3 NPN signals
With indicator light

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III
Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	2A
Signal points	8
Status Display	Yes

Connection data 1

Connection name	Control system side
Connection method	Screw connection
Connection volume	1
Number of digits	10
spacing	5.08mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	0.5mm² ... 1.5 mm²
Connectable guide cross section AWG	28-16AWG
Connection meets standards	UL1059
Connection method	Plug screw connection
Connection volume	8
Number of digits	3
screw thread	M2
Hard wire cross section	0.5mm² ... 1.5 mm²

Dimension

length	65.5mm
width	57mm

Height	35mm

Accessori

Dati aziendali

numero d'ordine	30040000012
Unità di imballaggio	2
Quantità di ordine minimo	10
Peso dei prodotti (senza imballaggio)	76