Panoramica

Informazioni sul prodotto



40A-GF-6.0-92116900025

40A silver gold female pins,Adapter wire specification6.0mm²

Vantaggi del prodotto

☑High-precision turning process, stable and reliable products;
☑Gold-plated and silver-plated are available, suitable for different environmental requirements;
☑Comprehensive products, resistant to temperature changes, shocks and harsh environments。

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

Marking

classification	Contact
Series	40A
Contact type	Crimping contact

versions

Female/Male	Female
manufacturing technique	Turning

Material characteristics

RoHS	Comply with RoHS exemptions
Plating material	Silver plated
Material	Copper alloy

Standards

Connection meets standards	EN 60664-1 IEC 61984

Technical specification

Conductor cross sections（mm²）	6.0mm²
Conductor cross sections(AWG)	10AWG
Working current	≤16A
Contact resistance	≤0.3mΩ
Plating Thickness	≥3μ"
Temperature range	-40℃~+125℃
Strip length	9.6mm
working life-mating cycles	≥500

Accessori

Dati aziendali

numero d'ordine	92116900025
Unità di imballaggio	100
Quantità di ordine minimo	100
Peso dei prodotti (senza imballaggio)	2.701