Überblick

Informationen zum Produkt



Interface module-DM50-IDC-10-10-4Y-00A(H)-30040000056

IDC module,input/output module,with screw connector and IDC stitching line,can be installed on DIN35 rail,10 positions

Produktvorteile

10digits to 50digits
1:1 connection
Screw connection

Zertifizierung von Produkten

Technische Daten

Produktzeichnung

3D-Modell

Dimension

length	66mm
width	57mm
Height	44mm

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3

Overvoltage category	III
Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	1A
Signal points	10
Status Display	no

Connection data 1

Connection name	Control system side
Connection method	IDC connection
Connection volume	1
Number of digits	10
spacing	2.54mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm² ... 2.5 mm²
Connectable guide cross section AWG	28-12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	10
screw thread	M3

Hard wire cross section	1.0 mm² ... 2.5 mm²

Zubehör

Accessories

Wire harness	DX211-1S-500-00A(H)

Die Geschäftsdaten

Nummer der Bestellung	30040000056
Verpackung Einheit	6
Minimale Bestellmenge	12
Produktgewicht (ohne Verpackung)	55