
DEGSON

## Überblick

### Informationen zum Produkt



# DSKK4-11040000064

Double-layer rail terminal, wiring method: direct insertion connection, rated voltage: 500 V, rated current: 32 A, connection quantity: 4, digit: 1, wiring capacity: 0.2 mm² - 6 mm², AWG: 24 - 10, width: 6.2 mm, color: gray, installation method: NS35/7.5, NS35/15

### Produktvorteile

☑Double-level terminal block.
☑Push-in connection technology, tool-free operation, more convenient and faster;
☑With orange wire button, one word or cross screwdriver can release wire.
☑Unique plug-in bridge, high circuit connection efficiency.
☑Optional marker to avoid wire mis-inserting.
☑Equipped with test holes for easy testing of the circuit.

### Zertifizierung von Produkten

## Technische Daten

### Produktzeichnung

### 3D-Modell

### Overview

| | |
|---|---|
| Connection method | Push in connection |
| Number of rows | 2 |
| number of connections | 4 |
| Open-end side panels | Yes |
| Insulation Materials | PA |
| Flame retardant grade, in line with UL 94 | V0 |

### Dimension

| | |
|---|---|
| NS 35/7,5 Height | 48.75mm |
| End plate width | 2.2mm |
| NS 35/15 Height | 56.25mm |
| length | 83.5mm |
| width | 6.2mm |

### Wiring data

| | |
|---|---|
| Strip length | 11~13mm |
| Conductor cross section solid | 0.2~6mm² |
| Conductor cross section flexible | 0.2~4mm² |
| Conductor cross section solid AWG | 24~10 |

### Environmental conditions

| | |
|---|---|
| Ambient temperature (operation) | -40 °C ~ 105 °C（depending on derating curve） |
| Relative humidity (storage/transport) | 25%~75% |

### IEC Electrical parameters

| | |
|---|---|
| Rated voltage (III / 3) | 500V |
| Rated current (III / 3) | 32A |
| Rated surge voltage | 6KV |

### Environmental protection

| | |
|---|---|
| REACh SVHC | Lead 7439-92-1 |
| RoHS | No excessive harmful substances |

## Zubehör

### Marker

| | |
|---|---|
| Top marker | / |
| Side marker | ZSF6 |

| | |
|---|---|
| Marker support | DMTH5-2 / DMTH5-3 |

Accessories

| | |
|---|---|
| Slotted screwdriver size (Blade thickness x Width) mm | 0.6x3.5 |
| Bridge | DFBXX-6.2 |
| End cover | D-DSKK4 |

Installation

| | |
|---|---|
| End clamp | E-WS N / E-PC-1100A |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail | NS35/7.5-1000-00A(H) |

Die Geschäftsdaten

| | |
|---|---|
| Nummer der Bestellung | 11040000064 |
| Verpackung Einheit | 50 |
| Minimale Bestellmenge | 50 |
| Produktgewicht (ohne Verpackung) | 16.41 |