## Überblick

### Informationen zum Produkt



# DS4-HE-LD24-11040000162

Fuse terminal blocks, connector method: Push-in connector, Fuse type: G / 5 x 20, Glass/ceramic/..., Rated voltage : 24 V,Rated current : 6.3 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm² - 6 mm², AWG: 24 - 10, Width: 6.2 mm, Color: black, Mounting type: NS35/7.5, NS35/15

### Produktvorteile

☑Fuse terminal blocks.
☑Push-in connection technology, tool-free operation, more convenient and faster;
☑With orange wire button, one word or cross screwdriver can release wire.
☑Snap-on fuse box for easy fuse replacement.
☑Equipped with LED indicator for quick identification of fusing status.
☑Equipped with dual-channel bridge wells, circuit connection testing is more flexible.
☑Equipped with test holes for easy testing of the circuit.

### Zertifizierung von Produkten

## Technische Daten

### Produktzeichnung

### 3D-Modell

### Overview

| | |
|---|---|
| Connection method | Push in connection |
| Number of rows | 1 |
| number of connections | 2 |
| Open-end side panels | Yes |
| Insulation Materials | PA |
| Flame retardant grade, in line with UL 94 | V0 |

| | |
|---|---|
| fuse | G/5 x 20 |
| Fuse type | Glass/ceramic/... |

Dimension

| | |
|---|---|
| NS 35/7,5 Height | 36.8mm |
| End plate width | 1.5mm |
| NS 35/15 Height | 44.3mm |
| length | 55.6mm |
| width | 6.2mm |

Wiring data

| | |
|---|---|
| Strip length | 11~13mm |
| Conductor cross section solid | 0.2~6mm² |
| Conductor cross section flexible | 0.2~4mm² |
| Conductor cross section solid AWG | 24~10 |

Environmental conditions

| | |
|---|---|
| Ambient temperature (operation) | -40 °C ~ 105 °C（depending on derating curve） |
| Relative humidity (storage/transport) | 25%~75% |

IEC Electrical parameters

| | |
|---|---|
| Rated current (Ill / 3) | 6.3A |

Environmental protection

| | |
|---|---|
| REACh SVHC | Lead 7439-92-1 |
| RoHS | No excessive harmful substances |

## Zubehör

Marker

| | |
|---|---|
| Top marker | ZB6 / ZS6 |

| | |
|---|---|
| Side marker | ZSF6 |
| Marker support | DTH5-25x5 / DTH5-25x12 |

Accessories

| | |
|---|---|
| Slotted screwdriver size (Blade thickness x Width) mm | 0.6x3.5 |
| Bridge | DFBXX-6.2 |
| End cover | D-DS4-HE |

Installation

| | |
|---|---|
| End clamp | E-WS N / E-PC-1100A |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail | NS35/7.5-1000-00A(H) |

Die Geschäftsdaten

| | |
|---|---|
| Nummer der Bestellung | 11040000162 |
| Verpackung Einheit | 100 |
| Minimale Bestellmenge | 100 |
| Produktgewicht (ohne Verpackung) | 9.705 |