Überblick

Informationen zum Produkt



Interface module-DT010-00A(H)-30040000095

16 positions input output module,with indicator light,with screw connector and IDC stitching line,can access 16 positionsNPN/PNP signal,can be installed on DIN35 rail

Produktvorteile

Suitable for 16-point (20-bit interface) controller， Screw connection

Zertifizierung von Produkten

Technische Daten

Produktzeichnung

3D-Modell

Dimension

length	65.5mm
width	57mm
Height	43mm

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III

Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	1A
Signal points	16
Status Display	Yes

Connection data 1

Connection name	Control system side
Connection method	IDC connection
Connection volume	1
Number of digits	20
spacing	2.54mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm² ... 2.5 mm²
Connectable guide cross section AWG	28-12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	18
screw thread	M3
Hard wire cross section	1.0 mm² ... 2.5 mm²

Zubehör

Accessories

Wire harness	DX213-1S-500-00A(H)

Die Geschäftsdaten

Nummer der Bestellung	30040000095
Verpackung Einheit	1
Minimale Bestellmenge	10
Produktgewicht (ohne Verpackung)	87