## Überblick

### Informationen zum Produkt



# MDR cable-DX220-1DS-500-00A(H)-23040000067

MDR cable,connector1:MDR slot connector（1×50 Core,180° output）,connector2:multi-Core Cable

### Produktvorteile

☑The cable is soft and has good bending resistance
☑Prefabricated connector, beautiful appearance
☑ Provide single-ended and double-ended cables
☑ Suitable for servo position control mode
☑ Save wiring time, and can achieve fast wiring with the company's interface module

### Zertifizierung von Produkten

## Technische Daten

### Produktzeichnung

### 3D-Modell

### Overview

| | |
|---|---|
| Single wire, number of twisted wires | 50 |
| Single stranded wire, material | Tinned copper |
| shield | Yes |
| Outer sheath, material | PVC |
| Outer sheath,color | black |

### Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -20 °C ... 80 °C |
| Ambient temperature (storage / transport) | -20 °C ... 80 °C |

### Standards/Regulations

| | |
|---|---|
| Flame retardant | ULVW-1 |
| Oil resistance | Oil resistant |
| Gasoline resistance | ≤246Ω/KM |
| Connection meets standards | UL758 |

Technical data

| | |
|---|---|
| Maximum allowable working voltage | 30VDC |
| Maximum current carrying capacity of each path | 0.7A |
| cable length | 0.5米 |
| Cable outer diameter | 6.5mm |
| Single strand, cross-sectional area | 0.08mm² |
| Single strand, cross section (AWG) | 28 |

Connection data 1

| | |
|---|---|
| Connection name | On-site side |
| Connection method | IDC/MIL female connector |
| Connection volume | 1 |
| Number of digits | 50 |
| spacing | 1.27mm |
| Exit angle | 180° |

Connection data 2

| | |
|---|---|
| Connection name | On-site side |
| Connection method | Multi-core wire |
| Connection volume | 1 |
| Number of digits | 50 |
| spacing | 1.27mm |

## Zubehör

## Die Geschäftsdaten

| | |
|---|---|
| Nummer der Bestellung | 23040000067 |
| Verpackung Einheit | 1 |
| Minimale Bestellmenge | 10 |
| Produktgewicht (ohne Verpackung) | 50 |