## Panoramica

### Informazioni sul prodotto



# TSB4-10070000035

Transformer terminal blocks,Rated current:32A.Rated voltage （III/2）:450V,Color:Orange ,Contact surface :Tin

### Vantaggi del prodotto

☑ Screw connection technology,safe and reliable
☑ Rail installation method,suitable for transformer wiring

### Certificazione del prodotto

## Dati tecnici

### Disegno del prodotto

### Modello 3D

### Connection capacity

| | |
|---|---|
| Conductor cross section solid | 0.5~4mm² |
| Conductor cross section flexible | 0.5~4.0mm² |
| AWG | 20~12AWG |
| Torque | 1.2N.m |
| Strip length | 9mm |

### Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 600V |
| Rated voltage (C) | 600V |
| Rated voltage (D) | 600V |

| | |
|---|---|
| Rated current (B) | 30A |
| Rated current (D) | 5A |
| Rated current (C) | 30A |

Electrical parameters IEC

| | |
|---|---|
| Rated current | |
| | 32A |
| Rated voltage(III/2) | 450V |
| Rated surge voltage(III/2) | 3KV |

Item properties

| | |
|---|---|
| Type of installation | panel |
| Connection method | Screw connection |
| Screwdriver | slotted-phillips screwdriver |
| screw thread | M4 |
| Number of potentials | 1 |
| Pluggable or not | no |
| Number of rows | 1 |

Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | copper |
| Contact point metal surface | tin-plated |
| Insulation Materials | PA66 |
| Insulating material group | I |
| Flammability rating | UL94V-0 |

Mechanical tests

| | |
|---|---|
| Test Specification | UL1059/IEC60998 |

### Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -40℃~105℃ |

## Accessori

### Accessories

| | |
|---|---|
| Coding strip | TZB4 |
| Bridge | / |
| Marking strip | / |
| Others | / |

### Tool

| | |
|---|---|
| Operating tool | / |
| Screwdriver | / |

## Dati aziendali

| | |
|---|---|
| numero d'ordine | 10070000035 |
| Unità di imballaggio | 100 |
| Quantità di ordine minimo | 30 |
| Peso dei prodotti (senza imballaggio) | 5 |