Panoramica

Informazioni sul prodotto



TSF2.5-10070000095

Transformer terminal blocks,Rated current:6.3A.Rated voltage （III/2）:250V,Color:Orange ,Contact surface :Tin

Vantaggi del prodotto

☑ Screw connection technology,safe and reliable
☑ Rail installation method,suitable for transformer wiring

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

Connection capacity

Conductor cross section solid	0.5~2.5mm²
Conductor cross section flexible	0.5~2.5mm²
AWG	20~14AWG
Torque	0.8N.m
Strip length	10mm

Electrical parameters UL

Rated voltage (B)	250V
Rated voltage (C)	250V
Rated voltage (D)	250V

Rated current (B)	6.3A
Rated current (D)	10A
Rated current (C)	6.3A

Electrical parameters IEC

Rated current	
	6.3A
Rated voltage(III/2)	250V
Rated surge voltage(III/2)	2KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M3.5
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998

Environmental data

Ambient temperature (operation)	-40℃~105℃

Accessori

Accessories

Coding strip	TSZB4
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Dati aziendali

numero d'ordine	10070000095
Unità di imballaggio	250
Quantità di ordine minimo	30
Peso dei prodotti (senza imballaggio)	9