
종람

제품 장점



## 5EDGVL-7.62-10020003460

Pluggable Terminal Blocks，Rated current：41A，Rated valtage（III/2）：630V，Pitch：7.62mm，Color：Green，Contact surface：Tin

제품 장점

☑ Universal installation method to ensure a high degree of flexibility in device design.
☑ The plug direction is perpendicular to the PCB.

제품 인증

기술 데이터

제품 도면

3D

Processing notes

| | |
|---|---|
| Process | Wave soldering/manual soldering |

Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 300V |
| Rated voltage (C) | 300V |
| Rated voltage (D) | 600V |
| Rated current (D) | 5A |

Electrical parameters IEC

| | |
|---|---|
| Rated voltage | 630V |
| Rated voltage(III/3) | 500V |

| | |
|---|---|
| Rated current | 41A |
| Rated voltage(III/2) | 630V |
| Rated voltage(II/2) | 1000V |
| Rated surge voltage(III/3) | 6KV |
| Rated surge voltage(III/2) | 6KV |
| Rated surge voltage(II/2) | 6KV |

Item properties

| | |
|---|---|
| Type of installation | PCB welding |
| Pin arrangement | Three rows in a straight line |
| Pitch | 7.62mm |
| Number of potentials | 2 |
| Pluggable or not | Yes |
| Number of rows | 1 |

Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | copper |
| Contact point metal surface | tin-plated |
| Contact zone metal surface | tin-plated |
| Insulation Materials | PBT |
| Insulating material group | IIIb |
| Flammability rating | UL94V-0 |

Mechanical tests

| | |
|---|---|
| Test Specification | IEC61984/ UL1059 |

Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -40℃~105℃ |

## 악세사리

### Tool

| | |
|---|---|
| Screwdriver | / |
| Operating tool | / |

### Accessories

| | |
|---|---|
| Coding strip | 2EDG-PWI |
| Bridge | / |
| Marking strip | / |
| Others | / |

## 비즈니스 데이터

| | |
|---|---|
| 발주 번호 | 10020003460 |
| 포장 단위 | 360 |
| MOQ | |
| 제품 무게 (포장 제외) | 6.17 |