
종람

제품 장점



## 15EDGVHM-3.81-10030000929

Pluggable Terminal Blocksnominal current7A.Rated voltage(Ⅱ/2):250V,pitch:3.81mm,Color:green,Contact surface:Tin

제품 장점

☑ Universal installation method to ensure a high degree of flexibility in device design
☑ Multi-layer wire connection can achieve higher contact density

제품 인증

기술 데이터

제품 도면

3D

Processing notes

| | |
|---|---|
| Process | Wave soldering/manual soldering |

Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 300V |
| Rated current (B) | 8A |

Electrical parameters IEC

| | |
|---|---|
| Rated voltage | 250V |
| Rated current | 7A |
| Rated voltage(Ⅱ/2) | 250V |
| Rated surge voltage(Ⅱ/2) | 2.5KV |

## Item properties

| | |
|---|---|
| Connection direction | 90° |
| Type of installation | PCB welding |
| Pin arrangement | Double-row in a straight line |
| Pitch | 3.81mm |
| Number of potentials | 8 |
| Pluggable or not | Yes |
| Number of rows | 2 |

## Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | Copper alloy |
| Contact zone metal surface | tin-plated |
| Insulation Materials | PA66 |
| Insulating material group | Ⅰ |
| Flammability rating | UL94V-0 |

## Mechanical tests

| | |
|---|---|
| Test Specification | IEC60947/UL1059 |

## Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -40℃~105℃ |

# 악세사리

## Tool

| | |
|---|---|
| Screwdriver | / |
| Operating tool | / |

## Accessories

| | |
|---|---|
| Coding strip | / |
| Bridge | / |
| Marking strip | / |
| Others | 15EDG-PWI |

## 비즈니스 데이터

| | |
|---|---|
| 발주 번호 | 10030000929 |
| 포장 단위 | |
| MOQ | |
| 제품 무게 (포장 제외) | |