
종람

제품 장점



8EDGD-7.5-10020002546

Pluggable terminal blocks,Rated current:20A.Rated voltage（III/3）:320V,pitch:7.5mm,Color:gray,Contact surface :Tin

제품 장점

☑ PCB welding, plug direction is perpendicular to the PCB
☑ Provides anti-touch protection for connection

제품 인증

기술 데이터

제품 도면

3D

Connection capacity

Strip length	6mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	320V
Rated voltage(III/3)	320V

Rated current	20A
Rated surge voltage(III/3)	4KV

Item properties

Connection direction	90°
Connection method	spring-cage connection
Pitch	7.5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	Ⅰ
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃

악세사리

Accessories

Coding strip	/

Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

비즈니스 데이터

발주 번호	10020002546
포장 단위	1050
MOQ	30
제품 무게 (포장 제외)	2.5