종람

제품 장점



15EDGVH-2.5-10030004125

Pluggable terminal blocks,Rated current:4A.Rated voltage（Ⅱ/2）:100V,pitch:2.5mm,Color:green,Contact surface :Tin

제품 장점

☑ Universal installation method to ensure a high degree of flexibility in device design
☑ Multi-layer wire connection can achieve higher contact density

제품 인증

기술 데이터

제품 도면

3D

Processing notes

Process	Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)	150V
Rated current (B)	5A

Electrical parameters IEC

Rated voltage	100V
Rated current	4A
Rated voltage(Ⅱ/2)	100V
Rated surge voltage(Ⅱ/2)	2.5KV

Item properties

Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Pitch	2.5mm
Number of potentials	4
Pluggable or not	Yes
Number of rows	2

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	Ⅰ
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃

악세사리

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	15EDG-PWI-2.5

비즈니스 데이터

발주 번호	10030004125
포장 단위	100
MOQ	30
제품 무게 (포장 제외)	1.82