
Overview

Product information



DBYR-04A63-C04-26020000006

630 series high voltage connector, rated operating current: 32A Max@4mm² 40A Max@6mm². Rated operating voltage: 1000V DC. Protection level: IP68, IP6K9K, IPXXB

Product advantages

☑ Wide applicability: It can be used in passenger cars and commercial vehicles, taking into account performance, space and cost-effectiveness.
☑ Strong compatibility: It can replace the same type of connectors on the market, and is compatible with functions such as wire throwing, welding plate, and single-ended waterproofing.
☑ High performance: Excellent waterproof performance, strong EMC performance, and excellent overcurrent capability.

Product certification

Technical data

Product drawing

3D model

Overview

shield	Yes

Environmental conditions

Maximum altitude	5000m(Above sea level)
Ambient temperature	-40℃...125℃
IP class	IP68

Signal feedback

HVIL	Yes

Versions

Number of positions	2

Electrical parameters IEC

Rated current	32A

Material data

Shell color	Orange
Flammability rating	UL94V-0

Durability test

Insert / pull out cycle	50

Electrical parameters

Rated current	40A
	1000V

Technical specification

Conductor cross sections（mm²）	4.0mm²
	6.0mm²

Accessories

Business data

Order number	26020000006
Packing unit	
Minimum order quantity	
Products weight (without packaging)	