
Przegląd

Informacje o produkcie



DGK12-111-13030000123

Building electronic housing ,length :53.6mm,DIN rail housing ,Upper housing with vent ,Can be used in distribution box comply with DIN 43880 standard , IP class:IP20.

Zalety produktu

☑Modern design
☑flexible PCB connection
☑high-efficiency DIN rail connector is optional
☑Support Wall-mounted installation and distribution power box installation in accordance with DIN 43880 standards

Certyfikacja produktu

Dane techniczne

Rysunek produktu

Model 3D

Dimensions

width	53.6mm
length	89.7mm
Height	60.7mm
Depth from top edge of DIN rail	54.7mm

PCB data

Number of PCB holders	15（Upper cover 6+Base 9）
PCB thickness	1.8mm
Installation location	Vertical &horizontal(DIN rail)
PCBType of installation	Latching

Item properties

IP class	IP20
Connection levels	1(Both sides)
with ventilation openings	Yes
Maximum connection	32 (pitch: 2.5 mm)；20 (pitch: 5 mm)；12 (pitch: 7.5 mm)

Material data

color	Upper housing: light gray bottom housing: black
Material	PC
Flammability rating	V2

Environmental data

Ambient temperature (assembly)	-5℃～ +100℃
Ambient temperature (operation)	-40℃～ +110℃
Ambient temperature (storage / transport)	-40℃～ +70℃

Akcesoria

Accessories

Dane biznesowe

numer zamówienia	13030000123
Jednostka opakowania	10
Minimalna ilość zamówienia	10
Waga produktów (bez opakowania)	50