DEGSON

## Przegląd

### Informacje o produkcie



# PM-M12A-05P-MM-SL8B01-20030000693

Sensor/Actuator Cable,PUR,black,UL20549,Male plug,Straight M12,Coding A,Unshielded,Trimming cable end,Cable Cable length:1m

### Zalety produktu

☑Sealing optimization, protection level up to IP68
☑Meet the harsh environment
☑Suitable for various occasions connection technology
☑Compatible with the international and domestic same series products

### Certyfikacja produktu

RoHS REACH

## Dane techniczne

### Rysunek produktu

### Model 3D

### Environmental conditions

| | |
|---|---|
| Ambient temperature | -25℃...80℃ |
| IP class | IP68 |

### General parameters

| | |
|---|---|
| Rated current | 4A |
| | 60V |
| Number of potentials | 5 |
| Insulation resistance | ≥ 100 MΩ |
| Error-proof coding | A-Code |

| | |
|---|---|
| Overvoltage level | II |
| Pollution level | 3 |
| Insertion and pullout cycle | ≥ 100 |
| Torque | 0.4 Nm |

Material

| | |
|---|---|
| Flammability rating ,in line with UL94 | V0 |
| Flammability rating ,in line with UL97 | HB |
| Contact material | CuZn |
| Material contact surface | Au |
| Contact carrier material | PU |
| Fixture body material | TPU |
| Coil material | Zinc alloy, nickel plated |
| Sealing material | Silicon |

Standards and specifications

| | |
|---|---|
| Standards/specifications | IEC 61076-2-101 |

Cable

| | |
|---|---|
| Cable type | PUR Black |
| Cable type(abbreviation) | PUR |
| UL AWM form | UL20549 |
| Cross section | 0.34mm² |
| AWG signal wire | 22AWG |
| Wire structure Signal wire | 17/0.16mm² |
| Core diameter (including insulation layer) | 1.30±0.05mm |
| Wire color | 1 Brown 2 White 3 Blue 4 Black 5 Gray |
| Thickness, insulation | 0.6mm |

| | |
|---|---|
| Cable outer diameter D | 5.4 ±0.2mm |
| Outer sheath, material | PU |
| Conductor insulation material | PE |
| Conductor material | Tinned copper |
| Insulation resistance | ≥100MΩ |
| Conductor resistance | Maximum 59.4Ω/km (at 20 °C) ) |
| Nominal cable voltage | 300V |
| Cable test voltage | 2000V |
| Flame retardant | Comply with UL 758/1581 FT2 standard |
| Oil resistance | No |

Dimension

| | |
|---|---|
| Cable length | 1m |

## Akcesoria

Accessories

| | |
|---|---|
| Sealing cap | CAP-M12-FP-8001 |

## Dane biznesowe

| | |
|---|---|
| numer zamówienia | 20030000693 |
| Jednostka opakowania | / |
| Minimalna ilość zamówienia | 100 |
| Waga produktów (bez opakowania) | / |