DEGSON

概要

製品情報



15EDGKDGB-3.5-10020007412

Pluggable terminal blocks,Rated current:12A.Rated voltage（III/2）:250V,pitch:3.5mm,Color:green,Contact surface :Tin

製品の特長

- ☑ Suitable for a variety of sockets
- ☑ PUSH-IN connection technology, quick wiring
- ☑ Both sides with operating rods, easy to pull out

製品認証

c UL us

技術データ

製品チャート

3Dモデル

Packaging information

Type of packaging	bag packaging

Connection capacity

Conductor cross section solid	0.2~1.5mm²
Conductor cross section flexible	0.2~1.5mm²
AWG	28~16AWG
Strip length	9mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	300V

Rated voltage (D)	300V
Rated current (B)	8A
Rated current (D)	8A
Rated current (C)	8A

Electrical parameters IEC

Rated voltage	250V
Rated current	12A
Rated voltage(III/2)	250V
Rated surge voltage(III/2)	2.5KV

Item properties

Connection method	Push-in spring connection
Screwdriver	Slotted screwdriver
Pitch	3.5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Relative tracking index CTI	600V
Shell color	green
Insulating material group	I

Flammability rating	UL94V-0
Mechanical tests	
Test Specification	IEC61984/ UL1059
Environmental data	
Ambient temperature (operation)	-40℃~105℃

アクセサリ

Tool	
Screwdriver	/
Operating tool	/
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	/

ビジネスデータ

注文番号	10020007412
パッキングユニット	600
最小注文数量	600
1個あたりの重量（梱包を含めない）	2.75