## 概要

### 製品情報



# 2EDGKT-5.0-10010002791

Pluggable terminal blocks,Rated current:20A.Rated voltage（III/2）:320V,pitch:5.0mm,Color:green,Contact surface :Tin

### 製品の特長

☑ Adapt to multi-type sockets, device design is highly flexible
☑ Keying parts can be installed
☑ Use the built-in test elements to test quickly and easily

### 製品認証

## 技術データ

### 製品チャート

### 3Dモデル

### Connection capacity

| | |
|---|---|
| Conductor cross section solid | 1.0~2.5mm² |
| Conductor cross section flexible | 1.0~2.5mm² |
| AWG | 30~12AWG |
| Strip length | 7mm |

### Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 300V |
| Rated voltage (D) | 300V |
| Rated current (B) | 18A |
| Rated current (D) | 10A |

## Electrical parameters IEC

| | |
|---|---|
| Rated voltage | 320V |
| Rated current | 20A |
| Rated voltage(III/2) | 320V |
| Rated surge voltage(III/2) | 4KV |

## Item properties

| | |
|---|---|
| Connection direction | 0° |
| Pin arrangement | Single row in a straight line |
| Connection method | Screw connection |
| Screwdriver | Slotted screwdriver |
| screw thread | M3 |
| Pitch | 5mm |
| Number of potentials | 2 |
| Pluggable or not | Yes |
| Number of rows | 1 |

## Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | Copper alloy |
| Contact point metal surface | tin-plated |
| Contact zone metal surface | tin-plated |
| Insulation Materials | PA66 |
| Insulating material group | I |
| Flammability rating | UL94V-0 |

## Mechanical tests

| | |
|---|---|
| Test Specification | IEC61984/ UL1059 |

| Environmental data | |
|---|---|
| Ambient temperature (operation) | -40℃~105℃ |

## アクセサリ

| Tool | |
|---|---|
| Screwdriver | 0.6x3.5，Slotted screwdriver |
| Operating tool | / |

| Accessories | |
|---|---|
| Coding strip | 2EDG-PWI |
| Bridge | DG019-5.0 |
| Marking strip | / |
| Others | / |

## ビジネスデータ

| | |
|---|---|
| 注文番号 | 10010002791 |
| パッキングユニット | 800 |
| 最小注文数量 | 30 |
| 1個あたりの重量（梱包を含めない） | 4 |