
## 概要

### 製品情報



# 15EDGKNHC-3.5-10020002839

Pluggable terminal blocks,Rated current:13.5A.Rated voltage（III/2）:160V,Cross section:1.5mm²,pitch:3.5mm,Color:green,Contact surface :Tin

### 製品の特長

- ☑ Adapt to multi-type sockets, device design is highly flexible
- ☑ PUSH-IN connection technology, fast wiring
- ☑ High-density double row, compact structure

### 製品認証

## 技術データ

### 製品チャート

### 3Dモデル

### Connection capacity

| | |
|---|---|
| Conductor cross section solid | 0.2~1.5mm² |
| Conductor cross section flexible | 0.2~1.0mm² |
| AWG | 24~16AWG |
| Strip length | 8mm |

### Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 300V |
| Rated current (B) | 8A |

### Electrical parameters IEC

| | |
|---|---|
| Rated voltage | 160V |
| Rated voltage(III/3) | 160V |
| Rated current | 8A |
| Rated voltage(III/2) | 160V |
| Rated voltage(II/2) | 320V |
| Rated surge voltage(III/3) | 2.5KV |
| Rated surge voltage(III/2) | 2.5KV |
| Rated surge voltage(II/2) | 2.5KV |

Item properties

| | |
|---|---|
| Connection direction | 0° |
| Connection method | Push-in spring connection |
| Pitch | 3.5mm |
| Number of potentials | 4 |
| Pluggable or not | Yes |
| Number of rows | 2 |

Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | Copper alloy |
| Contact point metal surface | tin-plated |
| Contact zone metal surface | tin-plated |
| Insulation Materials | PA66 |
| Insulating material group | I |
| Flammability rating | UL94V-0 |

Mechanical tests

| | |
|---|---|
| Test Specification | IEC61984/ UL1059 |

| Environmental data | |
|---|---|
| Ambient temperature (operation) | -40℃~105℃ |

## アクセサリ

| Accessories | |
|---|---|
| Coding strip | / |
| Bridge | / |
| Marking strip | / |
| Others | / |

| Tool | |
|---|---|
| Operating tool | / |
| Screwdriver | / |

## ビジネスデータ

| | |
|---|---|
| 注文番号 | 10020002839 |
| パッキングユニット | 600 |
| 最小注文数量 | 30 |
| 1個あたりの重量（梱包を含めない） | 2.23 |