
概要

製品情報



8EDGKRB-7.5-10020002748

Pluggable terminal blocks,Rated current:20A.Rated voltage（III/3）:400V,pitch:7.5mm,Color:gray,Contact surface :Tin

製品の特長

- ☑ Adapt to multi-type plugs, device design is highly flexible
- ☑ Cage clamp connection technology,fast wiring
- ☑ Universal installation method, suitable for various situations

製品認証

技術データ

製品チャート

3Dモデル

Connection capacity

Conductor cross section solid	0.2~2.5mm²
Conductor cross section flexible	0.2~2.5mm²
AWG	22~14AWG
Strip length	9mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A

Rated current (D)	10A

Electrical parameters IEC

Rated voltage	400V
Rated voltage(III/3)	400V
Rated current	20A
Rated surge voltage(III/3)	4KV

Item properties

Connection direction	0°
Type of installation	panel
Pin arrangement	Single row in a straight line
Connection method	spring-cage connection
Pitch	7.5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃

アクセサリ

Accessories

Coding strip	/
Bridge	DG018-7.5
Marking strip	/
Others	/

Tool

Operating tool	DG010
Screwdriver	/

ビジネスデータ

注文番号	10020002748
パッキングユニット	400
最小注文数量	30
1個あたりの重量（梱包を含めない）	4.5