
概要

製品情報



8EDGKG-3.81-10020002659

Pluggable terminal blocks,Rated current:10A.Rated voltage（III/3）:130V,pitch:3.81mm,Color:gray,Contact surface :Tin

製品の特長

- ☑ Adapt to multi-type sockets, device design is highly flexible
- ☑ Cage clamp connection technology,fast wiring
- ☑ Universal installation method, suitable for various situations

製品認証

技術データ

製品チャート

3Dモデル

Connection capacity

Conductor cross section solid	0.2~1.5mm²
Conductor cross section flexible	0.2~1.5mm²
AWG	28~14AWG
Strip length	6mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	10A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	130V
Rated voltage(III/3)	130V
Rated current	10A
Rated surge voltage(III/3)	2.5KV

Item properties

Connection direction	0°
Connection method	spring-cage connection
Pitch	3.81mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃

アクセサリ

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

ビジネスデータ

注文番号	10020002659
パッキングユニット	180
最小注文数量	30
１個あたりの重量（梱包を含めない）	2.25