概要

製品情報



15EDGVTM-3.81-10030001030

Pluggable Terminal Blocksnominal current7A.Rated voltage(Ⅱ/2):250V,pitch:3.81mm,Color:green,Contact surface:Tin

製品の特長

☑ Universal installation method to ensure a high degree of flexibility in device design
☑ Multi-layer wire connection can achieve higher contact density

製品認証

技術データ

製品チャート

3Dモデル

Processing notes

Process	Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)	300V
Rated current (B)	8A

Electrical parameters IEC

Rated voltage	250V
Rated current	7A
Rated voltage(II/2)	250V

Rated surge voltage(II/2)	2.5KV

Item properties

Connection direction	90°
Type of installation	PCB Soldering
Pin arrangement	Double-row in a straight line
Pitch	3.81mm
Number of potentials	6
Pluggable or not	Yes
Number of rows	2

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃

アクセサリ

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	15EDG-PWI

ビジネスデータ

注文番号	10030001030
パッキングユニット	
最小注文数量	
1個あたりの重量（梱包を含めない）	