
概要

製品情報



8EDGRC-2.5-10030002710

Pluggable terminal blocks,Rated current:6A.Rated voltage（III/3）:130V,pitch:2.5mm,Color:gray,Contact surface :Tin

製品の特長

☑ Universal installation method to ensure a high degree of flexibility in device design
☑ The plug direction is parallel to the PCB

製品認証

技術データ

製品チャート

3Dモデル

Processing notes

Process	Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)	150V
Rated voltage (C)	150V
Rated voltage (D)	150V
Rated current (B)	4A
Rated current (D)	4A
Rated current (C)	4A

Electrical parameters IEC

Rated voltage	130V
Rated voltage(III/3)	130V
Rated current	6A
Rated surge voltage(III/3)	2.5KV

Item properties

Connection direction	0°
Type of installation	PCB Soldering
Pin arrangement	Single row in a straight line
Pitch	2.5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃

アクセサリ

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

ビジネスデータ

注文番号	10030002710
パッキングユニット	500
最小注文数量	30
１個あたりの重量（梱包を含めない）	0.35