DEGSON

## 概要

### 製品情報



# 15EDGKC-3.5-10010000657

Pluggable terminal blocks,Rated current:8A.Rated voltage（II/2）:250V,pitch:3.5mm,Color:green,Contact surface :Tin

### 製品の特長

☑ Adapt to multi-type sockets, device design is highly flexible
☑ Keying requirements can be met
☑ Universal installation method, suitable for various situations

### 製品認証

c UL us

## 技術データ

### 製品チャート

### 3Dモデル

### Connection capacity

| | |
|---|---|
| Conductor cross section solid | 0.5~1.5mm² |
| Conductor cross section flexible | 0.75~1.5mm² |
| AWG | 30~16AWG |
| Torque | 0.2N.m |
| Strip length | 7mm |

### Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 300V |
| Rated current (B) | 10A |

### Electrical parameters IEC

| | |
|---|---|
| Rated voltage | 250V |
| Rated current | 8A |
| Rated voltage(II/2) | 250V |
| Rated surge voltage(II/2) | 2.5KV |

Item properties

| | |
|---|---|
| Connection direction | 0° |
| Connection method | Screw connection |
| Screwdriver | Slotted screwdriver |
| screw thread | M2 |
| Pitch | 3.5mm |
| Number of potentials | 2 |
| Pluggable or not | Yes |
| Number of rows | 1 |

Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | Copper alloy |
| Contact zone metal surface | tin-plated |
| Insulation Materials | PA66 |
| Insulating material group | Ⅰ |
| Flammability rating | UL94V-0 |

Mechanical tests

| | |
|---|---|
| Test Specification | IEC61984/ UL1059 |

Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -40℃~105℃ |

## アクセサリ

### Tool

| | |
|---|---|
| Screwdriver | 0.4x2.5,Slotted screwdriver |
| Operating tool | / |

### Accessories

| | |
|---|---|
| Coding strip | / |
| Bridge | / |
| Marking strip | / |
| Others | / |

## ビジネスデータ

| | |
|---|---|
| 注文番号 | 10010000657 |
| パッキングユニット | 1800 |
| 最小注文数量 | 30 |
| １個あたりの重量（梱包を含めない） | 2.642 |