
DEGSON

概要

製品情報



15EDGVM-5.08-10030001000

Pluggable Terminal Blocksnominal current7A.Rated voltage(Ⅱ/2):450V,pitch:5.08mm,Color:green,Contact surface:Tin

製品の特長

☑ Universal installation method to ensure a high degree of flexibility in device design
☑ The plug direction is perpendicular to PCB

製品認証

技術データ

製品チャート

3Dモデル

Processing notes

Process	Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)	300V
Rated current (B)	8A

Electrical parameters IEC

Rated voltage	450V
Rated current	7A
Rated voltage(Ⅱ/2)	450V
Rated surge voltage(Ⅱ/2)	4KV

Item properties

Connection direction	90°
Type of installation	PCB Soldering
Pin arrangement	Single row in a straight line
Pitch	5.08mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	Ⅰ
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃

アクセサリ

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	15EDG-PWI

ビジネスデータ

注文番号	10030001000
パッキングユニット	
最小注文数量	
1個あたりの重量（梱包を含めない）	