DEGSON

## 概要

### 製品情報



# 2EDGRHC-5.08-10030007811

Pluggable terminal blocks,Rated current:8A.Rated voltage（III/2）:400V,pitch:5.08mm,Color:black,Contact surface :Tin

### 製品の特長

☑ PCB welding base
☑ Flexible supporting a variety of plugs

### 製品認証

c UL us

## 技術データ

### 製品チャート

### 3Dモデル

### Packaging information

| | |
|---|---|
| Type of packaging | bag packaging |

### Processing notes

| | |
|---|---|
| Process | Reflow soldering/wave soldering/manual soldering |

### Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 300V |
| Rated voltage (D) | 300V |
| Rated current (B) | 10A |
| Rated current (D) | 10A |

### Electrical parameters IEC

| | |
|---|---|
| Rated voltage | 400V |
| Rated voltage(III/3) | 250V |
| Rated current | 8A |
| Rated voltage(III/2) | 400V |
| Rated voltage(II/2) | 630V |
| Rated surge voltage(III/3) | 4KV |
| Rated surge voltage(III/2) | 4KV |
| Rated surge voltage(II/2) | 4KV |

Item properties

| | |
|---|---|
| Type of installation | PCB Soldering |
| Pin arrangement | Double-row in a straight line |
| Pitch | 5.08mm |
| Number of potentials | 6 |
| Pluggable or not | Yes |
| Number of rows | 2 |

Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | copper |
| Contact zone metal surface | tin-plated |
| Insulation Materials | High temperature resistant materials |
| Relative tracking index CTI | 250V |
| Glow Wire Flammability Index GWFI | 850 |
| Shell color | Black |
| Insulating material group | IIIa |
| Flammability rating | UL94V-0 |

| Mechanical tests | |
|---|---|
| Test Specification | IEC61984/ UL1059 |
| **Environmental data** | |
| Ambient temperature (operation) | -40℃~120℃ |

## アクセサリ

| Tool | |
|---|---|
| Screwdriver | / |
| Operating tool | / |
| **Accessories** | |
| Coding strip | / |
| Bridge | / |
| Marking strip | / |
| Others | / |

## ビジネスデータ

| | |
|---|---|
| 注文番号 | 10030007811 |
| パッキングユニット | |
| 最小注文数量 | |
| 1個あたりの重量（梱包を含めない） | |