종람

제품 장점



## SD-M12A-04P-FF-SH8001-20030001080

Sensor/Actuator Female socket,M12,Coding A,Front panel installation/PG9 Thread mounted,Soldering cup

제품 장점

☑Sealing optimization, protection level up to IP68
☑Meet the harsh environment
☑Suitable for various occasions connection technology
☑Compatible with the international and domestic same series products

제품 인증

기술 데이터

제품 도면

3D

Environmental conditions

| | |
|---|---|
| Ambient temperature | -40℃...105℃ |
| IP class | IP68 |

General parameters

| | |
|---|---|
| Rated current | 4A |
| | 250V |
| Number of potentials | 4 |
| Insulation resistance | ≥ 100 MΩ |
| Error-proof coding | A-Code |

| | |
|---|---|
| Overvoltage level | II |
| Pollution level | 3 |
| Connection method | Soldering |
| Insertion and pullout cycle | ≥ 100 |
| Torque | 0.4 Nm |
| Type of installation | Installation in front of the board |

### Material

| | |
|---|---|
| Flammability rating ,in line with UL94 | V0 |
| Contact material | CuZn |
| Material contact surface | Au |
| Contact carrier material | PA |
| Coil material | Zinc alloy, nickel plated |
| Sealing material | Silicon |

### Standards and specifications

| | |
|---|---|
| Standards/specifications | IEC 61076-2-101 |

## 악세사리

### Accessories

| | |
|---|---|
| Sealing cap | CAP-M12-MP-8002 |

## 비즈니스 데이터

| | |
|---|---|
| 발주 번호 | 20030001080 |
| 포장 단위 | / |
| MOQ | 100 |
| 제품 무게 (포장 제외) | / |