
Overview

Product information



DM-RJ45-F-21020000084

Heavy-duty insert,Number of contacts:8,Dimension:1 module Spaces,Rated voltage :50V,Rated current:1A,Female insert,Crimping connector

Product advantages

☑Crimping connection technology, applicable to a wide range of wire specifications ;
☑Modular products, easy to assemble and maintain 。

Product certification

CE

Technical data

Product drawing

3D model

Marking

classification	Insert
Series	DM

Versions

Connection method	Crimping connection
Female/Male	Female
Dimension	1 module
Number of positions	8
PE Contacts	No

Material characteristics

Material（insert）	Polycarbonate（PC）
Materia（Contact）	Copper alloy
Surface（Contact）	Silver plated
Flammability rating	V-0
color	Grey/White（RAL 7032）
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	1A
	50V
Rated pulse voltage	0.8KV
Pollution level	3
On the basis of UL /CSARated current	30V
Insulation resistance	≥10000MΩ
Temperature range	-40℃~+85℃
working life-mating cycles	≥500 time

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984

Accessories

Business data

Order number	21020000084
Packing unit	100
Minimum order quantity	5
Products weight (without packaging)	23.8