
## Overview

### Product information



# WS2.5-QU-LD-100A(H)-11030000492

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Rated voltage: 250 V, Backward voltage： 1000V, Rated current: 0.5 A, Number of connectors: 4, Number of potentials: 1, Cross section: 0.2 mm² - 2.5 mm², AWG: 28 - 14, Width: 5 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

### Product advantages

☑WS Diode terminal；
☑spring-cage connection technology, good anti-vibration performance；
☑Use an ordinary flat-blade screwdriver, you can easily wire and take the wire；
☑Can be matched with marker strips to avoid incorrect insertion of wires。

### Product certification

## Technical data

### Product drawing

### 3D model

### Overview

| | |
|---|---|
| Connection method | spring-cage connection |
| Number of rows | 1 |
| number of connections | 4 |
| Open-end side panels | Yes |
| Insulation Materials | PA |
| Flame retardant grade, in line with UL 94 | V0 |
| Insulating material group | I |
| standard test | IEC60947-7-1 |

### Dimension

| | |
|---|---|
| width | 5mm |
| End plate width | 2.5mm |
| Height | 32.45mm |
| NS 35/7,5 Height | 35.45mm |
| NS 35/15 Height | 42.95mm |
| length | 75.5mm |

Wiring data

| | |
|---|---|
| Strip length | 8~9mm |
| Conductor cross section solid AWG | 28~14 |
| Conductor cross section solid | 0.2~2.5mm² |
| Conductor cross section flexible | 0.2~2.5mm² |
| 2 flexible conductors with a TWIN ferrule | 0.5mm² |

IEC Electrical parameters

| | |
|---|---|
| Rated voltage (III / 3) | 250V |
| Rated current (III / 3) | 0.5A |
| Rated surge voltage | 8KV |

UL Electrical parameters

| | |
|---|---|
| Rated voltage | / |
| Rated current | / |

Environmental conditions

| | |
|---|---|
| Ambient temperature (operation) | -40 °C ~ 105 °C（depending on derating curve） |
| Relative humidity (storage/transport) | 25%~75% |
| Ambient temperature (storage / transport) | -25℃~60℃ |

Mechanical performance test

| | |
|---|---|
| Mechanical strength | Passed the test |
| Fixing support | Passed the test |
| Rotational Pull Test | Passed the test |

Electrical performance test

| | |
|---|---|
| Voltage drop | ≤3.2mV |
| Temperature rise test | ≤45 K |

Safety test

| | |
|---|---|
| Anti-finger touch | Passed the test |

Environmental protection

| | |
|---|---|
| RoHS | No excessive harmful substances |
| REACh SVHC | Lead 7439-92-1 |

## Accessories

Marker

| | |
|---|---|
| Top marker | ZB5 / WB5 |
| Side marker | DEK5 |
| Marker support | DTH5-25×5 / DTH5-25×12 |
| Warning cover | EEA2.5 |

Accessories

| | |
|---|---|
| Slotted screwdriver size (Blade thickness x Width) | 0.5×3.5 |
| Adjacent jumper (2P) | / |
| Alternate jumper (2P) | / |
| Staggered jumper (2P) | / |
| End cover | D-WS2.5-QU |

Installation

| | |
|---|---|
| End clamp | E-WS N / E-PC-1100A |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail | NS35/7.5-1000-00A(H) |

Marking & Installation

| | |
|---|---|
| Marking strip | ZB5 |
| Marker cards | DBE-1 |

Accessories

| | |
|---|---|
| End cover | D-WS2.5-QU |
| End clamp | E-WS |
| DIN rail | NS35/7.5-1000-00A(H) |

## Business data

| | |
|---|---|
| Order number | 11030000492 |
| Packing unit | 50 |
| Minimum order quantity | 50 |
| Products weight (without packaging) | 9.372 |