Overview

Product information



PM-M8A-06P-FF-SR7C01-20020000263

Sensor/Actuator Cable,PVC,black,UL2517,Female plug,Angled,M8,Coding A,Unshielded,Trimming cable end,Cable Cable length:1m,UL Certification

Product advantages

☑Sealing optimization, protection level up to IP67
☑Meet the harsh environment
☑Miniature connector,Space saving
☑Suitable for various occasions connection technology
☑Compatible with the international and domestic same series products

Product certification

Technical data

Product drawing

3D model

Environmental conditions

Ambient temperature	-25℃...80℃
IP class	IP67

General parameters

Rated current	1.5A
	30V
Number of potentials	6
Insulation resistance	≥ 100 MΩ
Error-proof coding	A-Code

Overvoltage level	II
Pollution level	3
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Fixture body material	TPU
Coil material	Copper alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-104

Cable

Cable type	PVC Black
Cable type(abbreviation)	PVC
UL AWM form	UL2517
Cross section	0.14mm²
AWG signal wire	26AWG
Wire structure Signal wire	7/0.16mm²
Core diameter (including insulation layer)	1.00±0.05mm
Wire color	1 Brown 2 White 3 Blue 4 Black 5 Gray 6 Pink
Thickness, insulation	0.23mm
Cable outer diameter D	5.0 ±0.2mm

Minimum bend radius ,fixed installation	5*OD
Minimum bend radius ,mobile installation	10*OD
Bending radius	50.8mm
Outer sheath, material	PVC
Conductor insulation material	PVC
Conductor material	Tinned copper
Insulation resistance	≥ 20 MΩ
Conductor resistance	Maximum 150Ω/km (at 20 °C))
Nominal cable voltage	300V
Cable test voltage	2000V
Special attributes	Silicone-free
Flame retardant	Compliant with UL758
Halogen free	Yes
Other protection functions	Anti-UV

Dimension

Cable length	1m

Accessories

Business data

Order number	20020000263
Packing unit	/
Minimum order quantity	100
Products weight (without packaging)	/