
Overview

Product information



WS2.5-TW-TA-PE-11030000265

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Number of connectors: 3, Number of potentials: 1, Cross section: 0.2 mm² - 2.5 mm², AWG: 28 - 14, Width: 5 mm, Color: green-yellow, Mounting type: NS 35/7.5, NS 35/15

Product advantages

☑spring-cage connection technology, good anti-vibration performance;
☑Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
☑Grounding structure, protection circuit;
☑Can be matched with marker strips to avoid incorrect insertion of wires;
☑The bevel design reduces the bending radius and makes the wire connection more convenient。

Product certification

Technical data

Product drawing

3D model

Overview

Connection method	spring-cage connection
Number of rows	1
number of connections	3
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0
Insulating material group	I

standard test	IEC60947-7-2

Dimension	
width	5mm
End plate width	2.5mm
Height	40.50mm
NS 35/7,5 Height	43.70mm
NS 35/15 Height	51.20mm
length	50.5mm

Wiring data	
Strip length	8~9mm
Conductor cross section solid AWG	28~14
Conductor cross section solid	0.2~2.5mm²
Conductor cross section flexible	0.2~2.5mm²
2 flexible conductors with a TWIN ferrule	0.5mm²

IEC Electrical parameters	
Rated voltage(III/3)	/
Rated current(III/3)	/

IEC Electrical parameters	
Rated surge voltage	8KV

UL Electrical parameters	
Rated voltage	/
Rated current	/

Environmental conditions	
Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）
Relative humidity (storage/transport)	25%~75%

Ambient temperature (storage / transport)	-25℃~60℃

Mechanical performance test

Mechanical strength	Passed the test
Fixing support	Passed the test
Rotational Pull Test	Passed the test

Electrical performance test

Voltage drop	≤3.2mV
Temperature rise test	≤45 K

Safety test

Anti-finger touch	Passed the test

Environmental protection

RoHS	No excessive harmful substances
REACh SVHC	Lead 7439-92-1

Accessories

Marker

Top marker	ZB5 / WB5
Side marker	/
Marker support	DTH5-25×5 / DTH5-25×12
Warning cover	EEA2.5

Accessories

Slotted screwdriver size (Blade thickness x Width)	0.5×3.5
Adjacent jumper (2P)	/
Alternate jumper (2P)	/
Staggered jumper (2P)	/

End cover	D-WS2.5-TW-TA

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

Marking & Installation

Marking strip	ZB5
Marker cards	DBE-1

Accessories

End cover	D-WS2.5-TW-TA
End clamp	E-WS
DIN rail	NS35/7.5-1000-00A(H)

Business data

Order number	11030000265
Packing unit	100
Minimum order quantity	100
Products weight (without packaging)	12.452