종람

제품 장점



DG271R-10.0-DA-10060001988

PCB spring terminal blocks,Rated current:76A.Rated voltage（III/2）:1000V,pitch:10.0mm,Color:green,Contact surface :Tin

제품 장점

☑ PUSH-IN connection technology, fast wiring
☑ Different poles can be combined through the side lock
☑ Universal installation method, suitable for various situations

제품 인증

기술 데이터

제품 도면

3D

Processing notes

Process	Wave soldering/manual soldering

Connection capacity

Conductor cross section solid	0.2~16mm²
Conductor cross section flexible	0.2~16mm²
AWG	20~4AWG
Strip length	17mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V

Rated voltage (D)	600V
Rated current (B)	70A
Rated current (D)	5A
Rated current (C)	70A

Electrical parameters IEC

Rated voltage	1000V
Rated voltage(III/3)	1000V
Rated current	76A
Rated voltage(III/2)	1000V
Rated voltage(II/2)	1000V
Rated surge voltage(III/3)	8KV
Rated surge voltage(III/2)	8KV
Rated surge voltage(II/2)	8KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Double-row of misalignment
Connection method	Push-in spring connection
Pitch	10mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS

Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	Ⅰ
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃

악세사리

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

비즈니스 데이터

발주 번호	10060001988
포장 단위	165
MOQ	30

제품 무게 (포장 제외)	17.85