종람

제품 장점



PA-M12B-05P-FF-SL7001-20030000488

Field mounted,Female,Straight,M12,Coding B,Soldering connector,Cable
External cable diameter 4.0~8.0 mm

제품 장점

☑Sealing optimization, protection level up to IP67
☑Meet the harsh environment
☑Suitable for various occasions connection technology
☑Compatible with the international and domestic same series products

제품 인증

기술 데이터

제품 도면

3D

Environmental conditions

Ambient temperature	-25℃...105℃
IP class	IP67

General parameters

Rated current	4A
	60V
Number of potentials	5
Insulation resistance	≥ 100 MΩ
Error-proof coding	B-Code

Overvoltage level	II
Pollution level	3
Connection method	Soldering
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-101

Dimension

Assembled cable outer diameter	4.0-8.0mm
Assembled conductor cross section	0.25~0.52 mm²
	24~20 AWG

악세사리

Accessories

Sealing cap	CAP-M12-MP-8004

비즈니스 데이터

발주 번호	20030000488

포장 단위	/
MOQ	100
제품 무게 (포장 제외)	/