Overview

Product information



Interface module-DT086-00A(H)-30040000090

16 positions output module,I/O interface module,with indicator light,with screw connector,can access binary or ternary NPN signal,can be installed on DIN35 rail

Product advantages

Quick-plug wiring
Screw connection

Product certification

Technical data

Product drawing

3D model

Dimension

width	57mm
Height	35mm
length	111mm

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III

Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	2A
Signal points	16
Status Display	Yes

Connection data 1

Connection name	Control system side
Connection method	Screw connection
Connection volume	1
Number of digits	18
spacing	5.08mm

Connection data 2

Connection name	On-site side
Stripping length	7mm
Cross section of flexible conductor	0.5mm² ... 1.5 mm²
Connectable guide cross section AWG	28-16AWG
Connection meets standards	UL1059
Connection method	Plug screw connection
Connection volume	16
Number of digits	3
screw thread	M2
Hard wire cross section	0.5mm² ... 1.5 mm²

Accessories

Business data

Order number	30040000090
Packing unit	1
Minimum order quantity	10
Products weight (without packaging)	135