Overview

Product information



Relay Socket-DSRT-05A-F3-00A(H)-30020000061

DSRT Relay Socket, used for 1PDT relay, screw connection

Product advantages

- ☑ Screw base relay socket
- ☑ Safe isolation between coil and contacts
- ☑ 16A ,2PDT
- ☑ Separation of input & output

Product certification

Technical data

Product drawing

3D model

Dimension

width	16mm
length	80mm
Depth including bracket	61.5mm

Environmental data

Ambient temperature (operation)	-45℃～+85℃
Ambient temperature (storage / transport)	-40℃~+65℃

Technical data

Rated voltage UN	300V

Rated current IN	16A
Installation location	Arbitrary
Assembly instructions	DIN35 rail

Connection data 1

Connection name	enter
Connection method	Screw connection
Stripping length	7-8mm
screw thread	M3
Cross section of flexible conductor	0.5-2.5mm²
Connectable guide cross section AWG	20-14AWG

Connection data 2

Connection name	Output
Stripping length	7-8mm
Cross section of flexible conductor	0.5-2.5mm²
Connectable guide cross section AWG	20-14AWG
Connection method	Screw connection

Accessories

Business data

Order number	30020000061
Packing unit	25 SKT
Minimum order quantity	25 SKT
Products weight (without packaging)	22g