Overview

Product information



DG332J-5.0-10030004709

Needle connector,Rated current:12A,Rated voltage（Ⅲ/2）250V,pitch:5.0mm,Color:black,Contact surface:Tin

Product advantages

☑ Adapt to multi-type plugs, device design is highly flexible
☑ Universal installation method

Product certification

Technical data

Product drawing

3D model

Processing notes

Process	Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)	300V
Rated current (B)	10A

Electrical parameters IEC

Rated voltage	250V
Rated current	12A
Rated voltage(Ⅲ/2)	250V
Rated surge voltage(Ⅲ/2)	2KV

Item properties

Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Pitch	5mm
Number of potentials	11
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998

Environmental data

Ambient temperature (operation)	-40℃~105℃(depending on derating curve)

Accessories

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Business data

Order number	10030004709
Packing unit	#N/A
Minimum order quantity	30
Products weight (without packaging)	#N/A